



4015B2

NEWTEC

the world leaders

Model
4015B2

High performance
combination
weigher



New performance levels for solid fruit and vegetables

For potatoes, onions, carrots and similar products

- Sturdy structure in stainless steel
- Detachable pans for simple cleaning and service
- Flexible to handle large as well as small products
- Products from \varnothing 20mm to \varnothing 120mm, and carrots up to 230mm long
- Provides maximum output per m²
- 500g packs up to 110 packs per minute
- 2.5kg packs up to 85 per minute
- Touch screen programming
- Reinforced weigh pan flaps ensuring low noise level
- Compact touch control panel. Simple and user friendly
- New infeed system which ensures good distribution of product in the machine
- VarioSpeed ensures optimum running – also when product is fed irregularly

NEWTEC

the world leaders

Model 4015B2



NEWTEC A/S
Stærmosegaardsvej 18
DK-5230 Odense M
Denmark

T: +45 66 15 84 44
F: +45 66 15 44 39

sales@newtec.com
www.newtec.com

Technical Data

Air requirement: Connection: 3/8"
Min. pressure: 6 Bar (0,6 MPa)
Consumption: 100 NL/min

Electrical requirement: 230/400 VAC +(N)+PE

Noise level: 79 dB(A)

Weight: 850kg (weigher only)
1170kg (combination as on picture)

Capacity

Portions per min. up to:	0,5Kg	1 Kg	2,5Kg	5Kg
Onions	110	95	85	55
Potatoes	110	95	85	55
Carrots	95	85	75	

User friendly touch screen programming

- various language options
- ethernet connection

